FLASH

StrobeFX 1000 IP65 CRMX

series Art by FLASH



Product code: F7100777

Strobes

StrobeFX 1000 IP65 CRMX is a new version of StrobeFX enriched with two control modes (CRMX and W-DMX). The device is equipped with two light sources and TILT: 185°: 12 RGB sections (588 pcs. RGB LED diode 5050), 12 WHITE BEAM sections (144 pcs.WHITE LED diode 3535, temperature 6000K). The device provides smooth brightness control, CRI=72.8, independent shape pixel control functions, and a constant beam angle (RGB 150°) (Strobo 70°). Thanks to the IP65 waterproof class and active cooling, it works perfectly in outdoor conditions.

flash fixtures: We have our own database of ready-made fixtures. Check if your product is included in the database, or place an order by emailing us at **fixtures@flashpro.pl**

Product Specification

Power Source (AC)

Supply voltage **110-230V**
Maximum power consumption **4,35A**
Power consumption **1000W**
Power frequency **50-60Hz**

Light source

Type **LED (RGB)**
Quantity **588**
Type **LED (W)**
Quantity **144**
Color temperature **6000K**
Color Rendering Index (CRI) **72,8 STROBO BEAM**
Color Rendering Index (CRI) **26,4 AURA RGB**

Color Mixing System

LED (W) **8 bit**
RGB **8 bit**

Dimming

Dimming **8 bit**

Beam angle

Beam angle **Fixed (RGB 150 °)**
Beam angle **Fixed (Strobo 70°)**

Strobe - frequency

Frequency **0.289Hz - 16.76Hz**
Pulsating **Yes**
Random **Yes**

DMX control

Number of modes **4**
Number of channels **14-68**

Movement

Range TILT **185°**
Regulation **16 bit**

Modes of operation

DMX512 **Yes**
RDM **Yes**
Art-Net **Yes**
Auto control **Yes**
Master-slave **Yes**
W-DMX **Yes**
CRMX **Yes**

User Interface

Physical buttons **Yes**
LCD display **Yes**

Connectors

AC IN **TrueCon IP65**
AC OUT **TrueCon IP65**
DMX IN **3-pin DMX**
DMX OUT **3-pin DMX**
ETHERCON **IN**
ETHERCON **OUT**

Physical parameters

IP protection level **IP65**
Housing type **ABS**
Fixing **Integrated**
Fixing **Mounting hole**
Fixing **Security point**
Housing color **Black**
Cooling **Active**
Length [cm] **50**
Width [cm] **13,5**
Height [cm] **33**
Weight [kg] **12,8**

MOTORIZED ZOOM, XLR 3-PIN, TRUECON IP65, TRUECON, TILT LOCK, TILT, 16 BIT DIMMING, RGBW, PAN LOCK, PAN, MASTER-SLAVE, VARIABLE LIGHT ANGLE, IP65, DMX512, BLACK, CTO LIQUID, ACTIVE COOLING, AUTO CONTROL, ABS, W-DMX, CRMX

more info: www.flash-butrym.pl
e-mail: sales@flash-butrym.pl