FLASH

# WashFX 1000 IP65 CRMX

Wash

series Art by FLASH



Product code: F7100776

**WashFX 1000 IP65 CRMX** is a new version of WashFX enriched with two control modes (CRMX and W-DMX), equipped with two light sources: 19x40 RGBW and Ring RGB. The device provides smooth brightness control, rotating lenses on both narrow and wide zoom (kaleidoscope effect), built-in shapes and the perimeter of the housing accentuated with an RGB LED strip. Thanks to the IP65 waterproof class and active cooling, it works perfectly in outdoor conditions. In addition, WashFX allows you to change the angle of light (4°-30°), Range of movement (PAN: 540° TILT: 270°).

**flash fixtures:** We have our own database of ready-made fixtures. Check if your product is included in the database, or place an order by emailing us at **fixtures@flashpro.pl**

ETC · JANDS · Showtec · HOG4 · grandMA2 · ChamSys · wysiwyg · GDTF · DMX · .2 · grandMA3 · AVOLITES · VISTA 3 · DMXcat · OBSIDIAN · myDMX · CAPTURE · Depence2 · SSL 2 · DWG · MA LIGHTING

## Product Specification

### Power Source (AC)

Supply voltage **110-230V**
Maximum power consumption **4,35A**
Power consumption **1000W**
Power frequency **50-60Hz**

### Light source

Type **LED (RGBW)**
Quantity **19**
Power (W) **40**
Ring **LED (RGB)**
Color Rendering Index (CRI) **70,9**

### Color Mixing System

RGBW **8 bit**
RGBW **16 bit**
RGB **8 bit**

### Dimming

Dimming **16 bit**

### ZOOM

Zoom **Motorized (8 bit)**

### Beam angle

Beam angle **Range (4°-30°)**

### CTO

CTO **2500K - 8000K (Smooth)**

### Strobe - frequency

Frequency **1Hz-20Hz**
Pulsating **Yes**
Random **Yes**

### DMX control

Number of modes **18**
Number of channels **21-124**

### Movement

Range PAN **540°**
Range TILT **270°**
Regulation **16 bit**

### Modes of operation

DMX512 **Yes**
Auto control **Yes**
Master-slave **Yes**
W-DMX **Yes**
CRMX **Yes**

### User Interface

Physical buttons **Yes**
LCD display **Yes**

### Connectors

AC IN **TrueCon IP65**
AC OUT **TrueCon IP65**
DMX IN **3-pin DMX**
DMX OUT **3-pin DMX**

### Physical parameters

IP protection level **IP65**
Housing type **ABS**
Fixing **Integrated**
Housing color **Black**
Cooling **Active**
Length [cm] **43**
Width [cm] **26**
Height [cm] **57,5**
Weight [kg] **23,4**

MOTORIZED ZOOM, XLR 3-PIN, TRUECON IP65, TRUECON, TILT LOCK, TILT, 16 BIT DIMMING, RGBW, PAN LOCK, PAN, MASTER-SLAVE, VARIABLE LIGHT ANGLE, IP65, DMX512, BLACK, CTO LIQUID, ACTIVE COOLING, AUTO CONTROL, ABS, W-DMX, CRMX

more info: www.flash-butrym.pl
e-mail: sales@flash-butrym.pl