FLASH

# BEAM 17R IP65

Moving Heads BEAM

series DJ by FLASH



Product code: F7100809

**BEAM 17R IP65** is a BEAM moving head equipped with a 380 W discharge lamp, producing an intense, narrow 2° beam of light. It features a color wheel with 13 colors, 15 static gobo patterns, two rotating prisms (8-facet and 48-facet), a Frost filter, a Rainbow effect, and motorized Focus adjustment. The fixture offers 540° PAN / 270° TILT movement, a 1–20 Hz strobe, mechanical dimming, and an additional RGB LED ring. It supports DMX512, RDM, automatic programs, and sound control. The IP65-rated housing allows operation in both indoor and outdoor environments. Its extensive range of optical effects makes it an excellent choice for concerts, stage productions, and outdoor events.

**flash fixtures:** We have our own database of **ready-made fixtures.** Check if your product is included in the database, or place an order by emailing us at **fixtures@flashpro.pl**

## Product Specification

### Power Source (AC)

Supply voltage **100–240 V AC**
Power frequency **50–60 Hz**
Power consumption **500 W**

### Light Sources

Main light source type **17R Discharge Lamp**
Number of main light sources **1**
Main light source power **380 W**
Color temperature **8500 K**
Color Rendering Index (CRI) **65**
Additional Light Source Type **RGB LED Ring**

### Color Wheel

Number of Colors **13 + Open (White)**
Bidirectional Color Wheel Rotation **Yes**
Rotation Speed Adjustment **Yes**

### GOBO Wheel

Number of Static Gobos **15 + Open Position**
Gobo Shake Effect **Yes**

### Prisms

Number of Prisms **2**
Prism 1 **8-Facet Circular**
Prism 2 **48-Facet Circular**
Prism Rotation **Bidirectional**
Rotation Speed Adjustment **Yes**

### FROST filter

Filter Type **Light Frost**
Control **Motorized**

### Rainbow Effect

Rainbow Filter **Yes**
Control **Motorized**

### Dimming

Dimming Type **Mechanical**
Dimming Range **0–100%**
Dimming Control Resolution **8 bit**

### Beam angle

Beam angle **2°**

### Focus adjustment

Focus adjustment **Motorized**
Focus Control Resolution **8 bit**

### Strobe

Frequency **1–20 Hz**
Pulse effect **Yes**
Random effect **Yes**

### DMX control

Number of DMX Modes **1**
Number of DMX Channels **22**

### Movement (PAN/TILT)

PAN movement range **540°**
TILT movement range **270°**
PAN / TILT control resolution **16 bit**

### Modes of operation

DMX512 **Yes**
RDM **Yes**
Automatic Programs (Auto) **Yes**
Sound Control (Sound) **Yes**
Master/Slave **Yes**

### User Interface

Buttons **Capacitive (touch)**
Display **Color LCD**

### Connectors

AC IN **TrueCon IP65**
AC OUT **TrueCon IP65**
DMX IN **3-pin XLR IP65**
DMX OUT **3-pin XLR IP65**

### Physical parameters

IP protection level **IP65**
Housing material **ABS**
Housing Color **Black**
Mounting System **2 Mounting Brackets**
Cooling **Active**
Operating Temperature **−25°C to +40°C**
Length [cm] **36**
Width [cm] **31**
Height [cm] **59**
Weight [kg] **20**

DISCHARGE LAMP, PRISM, PAN, TILT, GOBO, MOTORIZED FOCUS, BLACK, AC, RGB LED RING, COLOR WHEEL, DMX512, RDM, IP65, TRUECON, 3-PIN XLR

more information: www.flash-butrym.pl
e-mail: sales@flash-butrym.pl