FLASH

ACTOR 600FR Auralis

series EVENT by FLASH



Product Code: F7100813

Moving Heads WASH

ACTOR 600FR Auralis is a professional moving-head Wash with a 200 mm Fresnel lens, designed for stage, theatre, and television productions. The 600 W RGBALW LED engine delivers full-spectrum colour mixing with natural colour rendering (CRI >97). A smooth 8°–30° linear zoom and frost filter allow seamless transitions from tight beams to wide washes. A 360° rotating prism, and a wide 1800K–10000K CCT range expand creative possibilities. 78 built-in LEE filters with crossfade, DMX512 control, and adjustable PWM ensure flicker-free, camera-ready operation. Silent performance (<38 dBA), precise PAN/TILT movement, and a robust design make Auralis ideal for live and broadcast use.

flash fixtures: We have our own database of **ready-made fixtures.** Check if your product is included in the database, or place an order by emailing us at **fixtures@flashpro.pl**

Product Specification

Power Source (AC)

Supply voltage **90-260V**
Power consumption **680W**
Power frequency **50-60Hz**

Light source

Type LED **(RGBALW)**
Quantity **1**
Power (W) **600**
Number of control sections **1**
Color Rendering Index (CRI) **>97**

Optics

Lens **Fresnel 200 mm**

Lux measurement

Light Output (5 m.): **8,890 lx @ 8°**
Light Output (5 m.): **1,580 lx @ 30°**

Color Mixing System

RGBALW **16 bit**
Gel LEE Library 1 Presets **78**
Gel LEE Library 2 Presets **78**
LEE Presets Crossfade **Yes**
CTC **1800K - 10000K**
TINT **Yes**

Dimming

Dimming **16 bit**

ZOOM

ZOOM Motorized **(8 bit)**
Zoom range **8°-30°**

Beam Angle

Beam Angle **(8°-47 °)**

FROST

Filtr Frost **Yes**

PRISM

Prism **Yes**
Prism Rotation **360 °**

Cooling

Fan Control **Yes**
Silent Mode **<38 dBA @ 1 m**

DMX control

Number of modes **2**
Number of channels **26-35**

Movement

Range PAN **540 °**
Range TILT **270 °**
Regulation **16 bit**

Modes of operation

DMX512 **Yes**
Sound control **Yes**
Auto control **Yes**
Master-slave **Yes**

User Interface

Buttons **Physical**
Display **2.4" LCD display**

Connectors

AC IN **PowerCON**
AC OUT **PowerCON**
DMX IN **3-pin XLR**
DMX OUT **3-pin XLR**

Physical parameters

IP protection level **IP20**
Housing type **ABS**
Fixing Mounting **hole**
Fixing **2 x Omega**
Blockade (Pan) **No**
Blockade (Tilt) **No**
Housing Color **Black**
Cooling **Active**
Length [cm] **38**
Width [cm] **27**
Height [cm] **46**
Weight [kg] **15,5**

AUTO CONTROL, AC, ABS, XLR 3-PIN, MOTORIZED ZOOM, SOUND CONTROL, POWERCON, MASTER-SLAVE, LED (RGBALW), IP20, DMX512, VARIABLE BEAM ANGLE

more info: www.flash-butrym.pl
e-mail: sales@flash-butrym.pl