FLASH

SOLO 200

series EVENT by FLASH



Moving heads SPOT

SOLO 200 is a compact, multifunctional LED moving head combining Beam, Spot and Wash effects. Equipped with a 200 W main LED light source with a color temperature of 9000 K and an additional 6 W RGB LED Ring, it offers a wide range of lighting effects. The fixture features a color wheel with 9 colors, 12 static and 7 rotating gobos, a 3-facet circular prism, motorized zoom and focus adjustment. The PAN range of 630° and TILT range of 270° enable dynamic movement, while DMX512, W-DMX and F-WDMX support provide flexible control options. Solo 200 is suitable for concerts, stage productions, club events and other live event applications.

Product code: F7100800

flash fixtures: We have our own database of **ready-made fixtures.** Check if your product is included in the database, or place an order by emailing us at **fixtures@flashpro.pl**

Product Specification

Power Source (AC)

Supply voltage **90-260 V AC**
Power frequency **50-60 Hz**
Power consumption **250 W**

Light source (LED)

Main light source type **LED**
Number of main light sources **1**
Main light source power **200 W**
Color temperature (CCT) **9000 K**
Color Rendering Index (CRI / Ra) **65**
Additional light source **LED Ring (RGB)**
Additional light source power **6 W**

Colors

Number of colors on the color wheel **9 + open**
Color wheel control resolution **8 bit**
Color mixing system **RGB (LED Ring)**
Color control resolution **8 bit**

Dimming

Dimming resolution **8 bit**

Zoom

Zoom adjustment **Motorized**
Zoom control resolution **8 bit**
Zoom range **5°–16°**

Beam angle

Beam angle (Beam / Spot) **2,5°-14°**
Beam angle (Wash) **14°-36°**

Focus adjustment

Focus adjustment **Motorized**
Focus control resolution **8 bit**

Prism

Prism type **Circular**
Number of facets **3**

GOBO Wheel

Number of static gobos **12 + open**
Number of rotating gobos **7 + open**
Gobo rotation control resolution **16 bit**

Strobe

Strobe frequency **1-20 Hz**

DMX control

Number of DMX Modes **3**
Number of DMX Channels **22-32**

Movement (PAN / TILT)

PAN movement range **630°**
TILT movement range **270°**
PAN / TILT control resolution **16 bit**

Modes of operation

DMX512 **Yes**
W-DMX **Yes**
F-WDMX **Yes**
Sound Control (Sound) **Yes**
Automatic Programs (Auto) **Yes**
Master/Slave **Yes**
IR Remote Control **Yes**

User interface

Display **Color**
Buttons **Physical**

Connectors

AC IN **PowerCON**
AC OUT **PowerCON**
DMX IN **3-pin XLR**
DMX OUT **3-pin XLR**

Physical parameters

IP protection level **IP20**
Housing material **ABS**
Housing Color **Black**
Cooling **Active**
Wireless DMX antenna **External**
Fixing **Omega Bracket**
Safety attachment point **Yes**
Length [cm] **31**
Width [cm] **22**
Height [cm] **43**
Weight [kg] **10,4**

AUTO CONTROL, AC, ABS, W-DMX, TILT, COLOR WHEEL, SOUND CONTROL, RC CONTROL, POWERCON, PAN, MASTER-SLAVE, LED (W), GOBO, FOCUS, VARIABLE FROST FILTER, DMX512, BLACK

more information: www.flash-butrym.pl
e-mail: sales@flash-butrym.pl