FLASH

PAR64 LED P300 +AUV F-WDMX



Kod produktu: P7100450

Reflectors LED PAR

flashPRO
INNOVATIVE STAGE LIGHTING

PAR64 LED P300 +AUV F-WDMX is equipped with a high-quality, bright COB 300W RGBW-AUV LED. No need to connect the headlights with cables to the control signal opens up countless possibilities for the user to use this device in places where the installation of lighting is significantly difficult or requires quick work. Where conditions make it impossible to run cables, the wireless DMX interface allows you to maintain communication and use the full spectrum of the spotlight's capabilities available only when controlled by DMX.Unique design, high quality of workmanship and materials ensuring high durability make this device a perfect tool for both demanding users and people who value simplicity and reliability. Many control modes, low weight of the device, LCD display - these are just a few of the features of this device. Additionally, the reflector is equipped with a universal double handle, which makes it very easy to hang it or simply place it on the ground.

flash fixtures: We have our own database of **ready-made fixtures.** Check if your product is included in the database, or place an order by emailing us at **fixtures@flashpro.pl**

Product Specification

Power Source (AC)

Supply voltage **100-245V**
Power consumption **300W**
Power frequency **50-60Hz**

Light source

Type LED **(RGBWAUV)**
Quantity **1**
Power (W) **300**
Number of control sections **1**

Color Mixing System

RGBWA+UV **8 bit - 16 bit**

Dimming

Dimming **8 bit - 16 bit**

Beam angle

Beam angle **Fixed (37°)**

Strobe - frequency

Frequency **1Hz-20Hz**

DMX control

Number of modes **10**
Number of channels **3-12**

Modes of operation

DMX512 **Yes**
Sound control **Yes**
Auto control **Yes**
Master-slave **Yes**
W-DMX/CRMX **Yes**

User Interface

Buttons **Physical**
Display **LCD display**

Connectors

AC IN **PowerCON**
AC OUT **PowerCON**
DMX IN **3-pin XLR**
DMX OUT **3-pin XLR**

Physical parameters

IP protection level **IP20**
Housing type **ABS**
Fixing **Integrated**
Housing Color **Black**
Cooling **Active**
Length [cm] **27**
Width [cm] **13**
Height [cm] **30**
Weight [kg] **3,8**

ACTIVE COOLING, AUTO CONTROL, AC, ABS, XLR 3-PIN, SOUND CONTROL, MASTER-SLAVE, FIXED BEAM ANGLE, IP20, DMX512, BLACK